

# VERTICAL FORM FILL & SEAL MACHINE VFFS-C95

The VFFS-C95 Vertical Fill Form & Seal machine is equipped with electronically thermo-controlled horizontal sealing bars, driven by Brushless motor, suitable for sealing heat-sealable films. Electronically thermo-controlled vertical sealing bar, operated by a pneumatic cylinder and film towing system with rubber tracks with cardan transmission, driven by an AC motor can be performed with variable speed.

The machine can be managed by touch control panel 10" and of course can fill several products (coffee, pet food, granular and powder food).



#### HIGHLIGHTS:

- Extremely flexible on bag sizes and package styles
- Top performance and reliability
- Ease of operation and quick change over and setup
- Minimal maintenance and easy cleaning



## ERRELLE s.r.l.







#### www.errelle.net

info@errelle.net sales@errelle.net

Via Loredano Bizzarri, 61 40010 Sala Bolognese (BO), Italy Tel. +39 051 6321855





VERTICAL FORM FILL & SEAL MACHINE VFFS-C95

#### TECHNICAL DATA:


MACHINE OUTPUT: 600 Kg/Hour.


OPTIONAL GROUPS:

- Electronic weighing machine
- Doser unit
- Aroma valve applicator
- 4 sealed corners device
- Nitrogen injection device
- Vertical sealing (as Stabilo pack)
- Injection print device
- Output belt

AIR PRESSURE:	6 bar
AIR CONSUMPTION:	< 200 NI/min
POWER INTALLED:	4 Kw
SUPPLY VOLTAGE:	400Vac + N - 50Hz
MACHINE WEIGHT:	850 Kg

#### MACHINE LAYOUT:





	Α	в	н
C95e-1 mm	1450	2500	1700
C95e-2 mm	1670	2550	1950

VFFS-C95

### ERRELLE s.r.l.

Via Loredano Bizzarri, 61 40010 Sala Bolognese (BO), Italy Tel. +39 051 6321855

#### MACHINE FORMAT RANGE:

VFFS-C95			
Max film-reel width	mm	680	
Max film-reel diameter	mm	500	
Bag width	mm	50-320	
Bag Length	mm	50-470	
Mechanical Speed up to	spm/bpm	80	

#### www.errelle.net

info@errelle.net sales@errelle.net